

SPIRATUBE **PUR**

Colour: Translucent with coppered steel spiral.

Temperature: - 40°C > + 90°C

Applications: Suction and discharge of abrasive powders, fumes, shavings, vapours and for heavy-duty industrial and abrasive applications.

Features: PU hose reinforced with a coppered steel spiral. Inside surface smooth. Considerable mechanical features. Very light and flexible. It allows a high resistance against abrasion and bending, thanks to the PU features, which are 5 times superior than the normal PVC. Weather resistant, suitable for most chemicals.

INSIDE DIA		WEIGHT	MIN WALL THICKNESS	BENDING RADIUS	VACUUM
mm & inch	g/m				
51	2"	250	0.4	40	2
57		300	0.4	50	1.7
63		310	0.4	55	1.7
76	3"	510	0.45	65	1.7
82		560	0.45	70	1.65
90		610	0.45	75	1.6
102	4"	650	0.5	85	1.3
110		690	0.5	90	1.2
115		730	0.5	95	1.1
127	5"	850	0.5	105	1
140		980	0.5	115	0.9
152	6"	1040	0.55	125	0.8
180		1450	0.55	150	0.5
203	8"	1650	0.55	165	0.4
228	9"	1900	0.55	185	0.4
254	10"	2150	0.6	210	0.4
305	12"	2650	0.6	250	0.3
356	14"	3050	0.6	300	0.3
406	16"	3500	0.6	350	0.3

* all diameters come in a standard roll length of 10 metres

This ducting is constructed to ensure uniform wall deformation through bends to improve flow rates. Bend uniformity and quality construction are hallmarks of the Spiratube range.

