

SPIRATUBE TPR

Colour: Black

Temperature: - 50°C > +120°C

Applications: Suction and discharge of abrasive powders, fumes, shavings, vapours and for heavy-duty industrial and abrasive applications (at high temperature).

Features: Flexible duct made of extruded thermoplastic rubber, reinforced with a steel spiral. Very light and flexible and is extremely resistant to high temperature, chemicals, abrasion and good UV resistance.

INSIDE DIA		WEIGHT	MIN WALL THICKNESS	BENDING RADIUS	VACUUM
mm & inch		g/m	mm	mm	m/H2O
51	2"	210	0.6	40	2
57		245	0.6	50	1.7
63		260	0.6	55	1.7
76	3"	390	0.6	65	1.7
82		410	0.6	70	1.65
90		450	0.6	75	1.6
102	4"	495	0.6	85	1.3
110		610	0.6	90	1.2
115		640	0.6	95	1.1
127	5"	690	0.6	105	1
140		810	0.6	115	0.9
152	6"	910	0.6	125	0.8
180		1210	0.6	150	0.5
203	8"	1320	0.6	165	0.4
228	9"	1490	0.6	185	0.4
254	10"	1800	0.6	210	0.4
305	12"	2100	0.6	250	0.3
356	14"	2450	0.6	300	0.3
406	16"	2800	0.6	350	0.3

* all diameters come in a standard roll length of 10 metres

This ducting is constructed to ensure uniform wall deformation through bends to improve flow rates. Bend uniformity and quality construction are hallmarks of the Spiratube range.

