

SPIRATUBE PUX

Colour: Translucent/clear

Temperature: -40°C to +90°C (maximum)

Applications: Suitable for woodworking machinery, CNC machinery, air, dust and fumes.

Features:

- Anti-static and food contact PU duct reinforced with a galvanised steel spring wire
- Surface Resistivity of $10^5 - 10^{12}$ ohms
- Medium walled, durable, flexible and highly compressible
- High level of abrasion resistance (5 times superior than PVC)



INTERNAL DIA		WEIGHT	MIN WALL THICKNESS	BENDING RADIUS	VACUUM	STANDARD LENGTH
mm & inch	g/m	mm	mm	m/H ₂ O	m	
76 3	380	0.4	30	1.7	10	
89 3½	450	0.4	35	1.6	10	
102 4	500	0.4	40	1.3	10	
115 4½	510	0.4	45	1.2	10	
127 5	560	0.5	55	1.0	10	
152 6	940	0.5	60	0.8	10	
178 7	1250	0.5	65	0.5	10	
203 8	1400	0.5	70	0.4	10	
254 10	1900	0.5	80	0.4	10	
305 12	2260	0.5	90	0.3	10	
356 14	2720	0.5	105	0.3	10	
406 16	3340	0.5	120	0.2	10	

*CAN BE MANUFACTURED IN UP TO 15M LENGTHS

This ducting is constructed to ensure uniform wall deformation through bends to improve flow rates. Bend uniformity and quality construction are hallmarks of the Spiratube range.